

DESCRIPTION

Good things are always better in a kit! Wallbox kits are the best option to take home the best for each charger at the best price.

Pulsar Plus is the smallest but most powerful smart EV charger from Wallbox. With 5 m power supply cable and up to 7.4 kW of power. Connect to the myWallbox app via wifi or Bluetooth to take advantage of all the smart charging features.

Compatible with your electric vehicle

Pulsar Plus is compatible with electric vehicles with type 2 charging plug.

Durability

Pulsar Plus, with IP54 and IK08 protection ratings, is water and dust resistant for safe indoor and outdoor installation.

Compact

Smaller than a toaster and lighter than a laptop

Powerful

Charging capacity up to 7.4 kW.

Connected

Connect Pulsar Plus to any smart device via wifi or Bluetooth and access the myWallbox app to control the charger with ease.

Controlled

Schedule charging sessions to take advantage of reduced off-peak rates, monitor charging status and enjoy many more benefits with the myWallbox app.

Integrated intelligence

Offline areas in your garage or parking spot are no longer a problem. Pulsar Plus incorporates Bluetooth to manage charging even if you can't connect to the network.

Cable holder

Holder for Wallbox charging cables, made of aluminum. Allows you to keep everything tidy by easily winding up the cable when charging is complete. Incredibly easy to install thanks to a 2-screw mounting system.

Power booster included



This pack includes a single-phase toroidal power meter to activate the Power Boost functionality and optimise the charging of your electric vehicle. It will detect the power consumed so as not to exceed the maximum power contracted in the installation and avoid tripping the automatic circuit breaker (causing a power outage) in the home or surprises at the end of the month due to over-consumption. In this way, you can control the total energy consumption of your household to allocate the right amount to recharge your electric car: the meter can increase the charging speed when there is more power available (for example, at night) or adjust it according to the consumption of your appliances.

Technical information

- Connector: Type 2
- Maximum current: 32 A, 5x10 mm² cable
- DC leakage detector included: Yes
- User interface: myWallbox Portal, Wallbox App
- Surge category: CAT III
- Storage temperature: -40°C to 70°C (-40°F to 158°F)
- RCCB: External RCCB required
- Rated frequency: 50 Hz / 60 Hz
- Degree of protection: IP54 / IK08
- Operating temperature: -25°C to 40°C (-25°F to 104°F)
- Input voltage: 110 / 230 V AC ± 10% (1P) / 400 V AC ± 10% (3P)
- Included features: Power Boost, Power Sharing Smart
- Dimensions: 166x163x82mm
- Maximum Power: 7.4kW
- Charging Mode: Mode 3
- Charger status information: Halo RGB LED, Wallbox App, myWallbox Portal
- Cable length: 5m
- Colour: White
- Accessories included: Single-phase clamp power meter 100A/SPM1-100-AC/TEMCO, Cable holder

TECHNICAL SPECIFICATIONS.

Color White

STRENGTHS